



QUALITEK®

No Clean De-Soldering Wick

DESCRIPTION

Qualitek No Clean Wick is designed for the repair of Printed Circuit Assemblies without the need for subsequent cleaning operations.

- Supplied on Static Dissipative Spools
- Fast Solder Absorption
- Low Residues Which are Clear, Non-Corrosive and Non-Hygroscopic.
- Excellent Shelf Life
- Flux J-STD 004 Classification ORL0

APPLICATION METHODS

While maintaining soldering iron at operating temperature, Place the Qualitek No Clean Wick over the Solder that requires removal and then place the soldering iron tip on to the top of the copper braid.

The solder joint and soldering braid will both heat up until the solder melts and is absorbed on to the Copper braid

through Capillary action. When finished remove from the solder joint surface and then cut off the solder contaminated braid ready for the next job.

PACKAGING & AVAILABILITY

Solder Wick is supplied in a vacuum package of 25 off Anti static plastic spools.

Each Spool is wound with 1.5m of de-soldering braid and is available in three standard widths, 1.9mm, 1.4mm and 0.6mm for very fine SMT applications.

Also available on larger spools to special order.

STORAGE & DISPOSAL

Solder wick can be stored in its vacuum packaging for many years and then used within six months of opening the package. Disposal should be in accordance with Local waste material requirements.

Qualitek® is a trademark of Qualitek International, Inc.

TEL: +44 (0) 151 334 0888 FAX: +44 (0) 151 346 1408 E-mail: sales@qualitek-europe.com Internet: www.qualitek.com
9 Apex Court, Bassendale Road, Wirral International Business Park, Bromborough, Wirral, CH62 3RE

QUALITEK

WORLDWIDE BRANCHES: UNITED KINGDOM – MEXICO – CHINA – PHILIPPINES – SINGAPORE-USA

This data is based on information that the manufacturer believed to be reliable and offered in good faith. Qualitek International, Inc. makes no warranties expressed or implied as to its accuracy and assumes no responsibilities and liabilities arising out of its use by others as conditions and methods of use of the products is beyond the control of Qualitek International, Inc. The user must determine the suitability of the product before using it on a commercial basis. The warranties extend only to the conformity of the product to the physical descriptions. In no event will Qualitek International, Inc. be responsible for special, incidental and consequential damages whether the claim is in contract, negligence or otherwise.