

Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

#### **SECTION 1. IDENTIFICATION**

Product name : DOW CORNING(R) SE 4422

000000000002507544

Product code : DCC000001874

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road

Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

# **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Not a hazardous substance or mixture.

### **GHS Label element**

Not a hazardous substance or mixture.

Precautionary Statements : Prevention:

P271 Use only outdoors or in a well-ventilated area.

Other hazards

None known.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone

Sealant

# Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Methyltrimethoxysilane treated aluminum oxide	Not Assigned	>= 70 - < 90
Carbon black	1333-86-4	>= 0.1 - < 1



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Silicon oxides Metal oxides Formaldehyde

Specific extinguishing meth-

ods

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Personal precautions, protec: : Follow safe handling advice and personal protective equip-

ment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methyltrimethoxysilane treated aluminum oxide	Not Assigned	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Respirable fraction)	1 mg/m3 (Aluminum)	ACGIH
Carbon black	1333-86-4	TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	3 mg/m3	ACGIH

# Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm	NIOSH REL
			260 mg/m3	
		ST	250 ppm	NIOSH REL
			325 mg/m3	
		TWA	200 ppm 260 mg/m3	OSHA Z-1

**Engineering measures** 

: Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

# Personal protective equipment

Respiratory protection

: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.

Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may re-

quire added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or

contact the Dow Corning customer service group.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Color : gray

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

 $: > 100 \, ^{\circ}\text{C}$ 

Flash point :  $> 100 \, ^{\circ}\text{C}$ 

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 2.15

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 500 Poise

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Methyl alcohol is formed upon contact with water or humid air. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapors. Safe handling conditions may be maintained by keeping vapor concentrations within the occupational exposure limit for

formaldehyde.

Formaldehyde may cause cancer. It is also toxic by

inhalation, skin absorption and ingestion, corrosive to skin and

eyes, and may cause skin sensitization and respiratory

irritation.

See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed upon

contact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

Water

Hazardous decomposition products

Contact with water or hu- : Methanol

mid air

Thermal decomposition : Formaldehyde

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

# **Acute toxicity**

Not classified based on available information.

# Ingredients: Carbon black:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

#### Skin corrosion/irritation

Not classified based on available information.

# **Ingredients:**

# Carbon black: Species: Rabbit

Result: No skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

# **Ingredients:**

# Carbon black: Species: Rabbit

Result: No eye irritation



Date of last issue: -Version **Revision Date:** MSDS Number:

12/18/2014 978010-00001 Date of first issue: 12/18/2014 1.0

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

# **Ingredients:**

# Carbon black:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

# Germ cell mutagenicity

Not classified based on available information.

# Ingredients:

# Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

# Carcinogenicity

Not classified based on available information.

#### Ingredients:

# Carbon black: Species: Rat

Application Route: Inhalation Exposure time: 2 Years Result: positive

Target Organs: Lungs

Remarks: The substance is inextricably bound in the product and therefore does not contribute

to a dust inhalation hazard.

Carcinogenicity - Assess-

ment

: Sufficient evidence of carcinogenicity in inhalation studies with

animals

**IARC** Group 2B: Possibly carcinogenic to humans

> Carbon black 1333-86-4

**OSHA** No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

**NTP** No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### Reproductive toxicity

Not classified based on available information.



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### Ingredients:

#### Carbon black:

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d

or less.

# Repeated dose toxicity

# Ingredients:

# Carbon black:

Species: Rat NOAEL: 1 mg/m3 LOAEL: 7 mg/m3

Application Route: Inhalation Test atmosphere: dust/mist Exposure time: 90 d

Remarks: The substance is inextricably bound in the product and therefore does not contribute

to a dust inhalation hazard.

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

# **Ingredients:**

# Carbon black:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 5,600 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

# Persistence and degradability

No data available

# **Bioaccumulative potential**

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

# **Disposal methods**

Resource Conservation and

Recovery Act (RCRA)

: This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

# **SECTION 14. TRANSPORT INFORMATION**

### **International Regulation**

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

# **IMDG-Code**

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

# **49 CFR**

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

# EPCRA - Emergency Planning and Community Right-to-Know



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# **US State Regulations**

### Pennsylvania Right To Know

Methyltrimethoxysilane treated aluminum Not Assigned 70 - 90 % oxide

Dimethyl siloxane, methyldimethoxy- 68037-58-1 20 - 30 %

New Jersey Right To Know

Methyltrimethoxysilane treated aluminum Not Assigned 70 - 90 %

oxide

Dimethyl siloxane, methyldimethoxy- 68037-58-1 20 - 30 %

terminated

terminated

Carbon black 1333-86-4 0.1 - 1 %

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other

reproductive defects.

# The ingredients of this product are reported in the following inventories:

KECI : All ingredients listed, exempt or notified.

REACH : All ingredients (pre-)registered or exempt.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

TSCA : All chemical substances in this material are included on or

exempted from listing on the TSCA Inventory of Chemical

Substances.

NZIoC : All ingredients listed or exempt.


#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

# **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 12/18/2014



Version Revision Date: MSDS Number: Date of last issue: -

1. 0 12/18/2014 978010-00001 Date of first issue: 12/18/2014

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8